



SERELIS



SERELIS



ISECO, to enjoy nice and healthy food.

Therefore, the preservation of food quality as well as the pleasure and safety of your customers will always remain at the heart of our concerns.

SERELIS, The user-friendly trolley for "A la Carte" service of meals in dining rooms or cafeterias. SERELIS trolleys ensure the preservation and serving of meals with perfect respect for temperature regulations and hygiene for hot and cold food storage.

- Capacity

Optimized capacity with the SERELIS line, 7 and 8 levels GN 1/1 and SERELIS Compact, 7 and 8 levels, GN 1/2.

- Integrated Refrigeration

Refrigeration of one or both cavities ensured by a state of the art compressor which is integrated and assembled on a rack to simplify maintenance.

- Easy to Use

Refrigeration cycles and temperatures can be either pre-programmed or manually programmed. It is possible to program the shelves level by level with 3 different temperature pre-settings. The small size of SERELIS and its 6 wheels allow for exceptional manoeuvrability.



• Thermocontact

The thermocontact, invented and improved over the years by ISECO, is the only existing system that smoothly resets temperatures while delivering quality results.

SERELIS allows simultaneous temperature resetting and maintenance for regular or special products, in several or individual portions, for a single cycle thanks to the possible pre-selection of three different temperatures inside the same cavity. The stability of the heating shelves ensures that the temperature is maintained, even after the trolley is unplugged.

Retherm precision allows the use of all types of containers : aluminium or polypropylene disposables or porcelain or stainless steel plates in all shapes and sizes.

The new thermocontact shelves, developed for SERELIS, allow a new refrigeration cycle to be ensured in less than two hours after the end of retherming.

• Hygiene

All HACCP guidelines for hygiene and cleaning are met : in the heating cavity, the thermocontact shelves block has been designed to pivot out for complete accessibility of the retherming compartment.

The new thermocontact shelves with integrated resistances offer a smooth surface for easy cleaning.

In the cooling cavity, the sliding rack is completely removable for the same purpose.



SERELIS RESTO

SERELIS Resto and SERELIS compact Resto have a unique working design for use in wards and dining rooms.

• Energy saving

Operating SERELIS is very energy efficient ; each shelf is individually regulated by programmable thermostat.


• Tracking

The onboard control panel displays the temperature in the cavities in real time as well as the time left in the retherm cycle and any interruptions to the cycle. The HACCP program option records the temperature during all phases of the cycle. This data is then radioed to a PC for review and record.
























SERELIS

SERELIS and SERELIS Compact are extremely versatile enabling the connection between production units and wards. Their reinforced chassis ensure a strong protection and can also be equipped with a mechanical traction system.



Technical characteristics SERELIS and SERELIS RESTO

		Nb of shelves	L	w	h	Power (w)
SERELIS 7.2 Isolé		7	1460	680	1020	5250
SERELIS 8.2 Isolé		8	1460	680	1020	6000
SERELIS 7.2.1 Fresh		7	1460	680	1020	5650
SERELIS 8.2.1 Fresh		8	1460	680	1020	6400
SERELIS 7.2 Fresh		7	1460	680	1020	6425
SERELIS 8.2 Fresh		8	1460	680	1020	7175
SERELIS 7 Isolé		7	1050	680	1020	5250
SERELIS 8 Isolé		8	1050	680	1020	6000
SERELIS 7 Fresh		7	1050	680	1020	6090
SERELIS 8 Fresh		8	1050	680	1020	6840
SERELIS Compact 7.2 Isolé		7	1290	680	1020	3500
SERELIS Compact 8.2 Isolé		8	1290	680	1020	4000
SERELIS Compact 7.2.1 Fresh		7	1290	680	1020	3900
SERELIS Compact 8.2.1 Fresh		8	1290	680	1020	4400
SERELIS Compact 7.2 Fresh		7	1290	680	1020	4475
SERELIS Compact 8.2 Fresh		8	1290	680	1020	4975
SERELIS Compact 7 Isolé		7	890	680	1020	3500
SERELIS Compact 8 Isolé		8	890	680	1020	4000
SERELIS Compact 7 Fresh		7	890	680	1020	4140
SERELIS Compact 8 Fresh		8	890	680	1015	4640

		Nb of shelves	L	w	h	Power (w)
SERELIS Resto 7.2 Isolé		7	1400	680	970	5250
SERELIS Resto 8.2 Isolé		8	1400	680	970	6000
SERELIS Resto 7.2.1 Fresh		7	1400	680	970	5650
SERELIS Resto 8.2.1 Fresh		8	1400	680	970	6400
SERELIS Resto 7.2 Fresh		7	1400	680	970	6425
SERELIS Resto 8.2 Fresh		8	1400	680	970	7175
SERELIS Resto 7 Isolé		7	990	680	970	5250
SERELIS Resto 8 Isolé		8	990	680	970	6000
SERELIS Resto 7 Fresh		7	990	680	970	6090
SERELIS Resto 8 Fresh		8	990	680	970	6840
SERELIS Resto Compact 7.2 Isolé		7	1250	680	970	3500
SERELIS Resto Compact 8.2 Isolé		8	1250	680	970	4000
SERELIS Resto Compact 7.2.1 Fresh		7	1250	680	970	3900
SERELIS Resto Compact 8.2.1 Fresh		8	1250	680	970	4400
SERELIS Resto Compact 7.2 Fresh		7	1250	680	970	4475
SERELIS Resto Compact 8.2 Fresh		8	1250	680	970	4975
SERELIS Resto Compact 7 Isolé		7	850	680	970	3500
SERELIS Resto Compact 8 Isolé		8	850	680	970	4000
SERELIS Resto Compact 7 Fresh		7	850	680	970	4140
SERELIS Resto Compact 8 Fresh		8	850	680	970	4640



ISECO SAS 63 route de Chamoy • 10130 SAINT-PHAL FRANCE
Tél. +33 3 25 42 55 55 • Fax +33 3 25 42 19 59

ISECO International 2, avenue de Kaarst
Euralliance Porte A • BP 52004 • 59777 EURALILLE
Tél. : + 33 3 59 35 20 85 • Fax : +33 3 59 35 20 86

Web site: www.iseco.fr • E-mail : contact@iseco.fr